

U.S.SAWS Heavy Duty Dust Buggy - Joint Clean-out

The U.S.SAWS Heavy Duty Dust Buggy is designed to clean-out existing control joints before filling or remove failing or deteriorated epoxy, polyurea, or polyurethane joint fillers. The joint clean-out saw cuts up to 2" deep with an 8" blade. Its up-cut rotation allows debris to be removed from joints as your moving forward. The polyurethane wheels help the Dust Buggy track perfectly straight. This model is made with a heavy-duty cast aluminum alloy chassis to hold up the most abusive environments.



Features

- Ideal for joint clean-out, joint filler removal, decorative concrete, and concrete cutting
- With the Tiger Tooth blades or PCD milling blade, this machine will remove polyurea joint filler
- Adjustable blade depth with up to 2" cutting depth (with 8" blade)
- Powered by a Metabo 15 Amp W24-230
- Up-cut blade rotation cleans debris out of the joint
- Durable and stable machine to allow for straight, accurate cuts
- Vacuum port allows for dust-free operation



Open Blade Option



Metabo Grinder



Pointer for Precision



Aluminum Frame

Model	Heavy Duty Dust Buggy
Part Number	SX13590
Grinder Make/ Model	Metabo W24-230
Output Power	15 Amp Electric
Max RPM	6,600
Power Requirements	115V, 60Hz
Max Cutting Depth	2"
Blade Diameter	7" or 8" Dry Diamond

