# U.S.SAWS™

## U.S.SAWS JS-131 Joint Clean-out Saw



U.S.SAWS JS-131 Gas – Joint Cleanout Saw is a gas-powered walk-behind used for joint cleanout, concrete sawing, and trench cutting. The material is milled out of the joint in an upward direction and is collected by the debris collection port. It features a blade guard design with upcut rotation, which permits easy dust extraction. A dust collector with a minimum of 350 CFM is recommended for use with this machine. Production speed is significantly dependant upon job site conditions.



Hose Port



Blade Spacers



Blade Guard



Honda Gas Engine

*Features:*

- Gas walk-behind mill used for joint clean out, concrete sawing, and trench cutting
- Up cut blade rotation with vacuum port on the front of the blade guard allows for easy and efficient dust collection
- This machine is designed to mill out dirt and debris from existing control joints prior to filling, or to remove existing joint fill material in need of replacement
- A dust collector with a minimum of 350 CFM is recommended but *225 CFM is acceptable for use with this machine
- Production speed is greatly dependant upon job site conditions

| Model | JS-131 |
|---|---|
| Part Number | SX77131 |
| Power Source | 13 HP Honda Gas |
| Max RPM | 5,850 |
| Max Cutting Depth | 3” |
| Blade Diameter | 8” or 10” Dry Diamond |
| Blade Width | .090”, .125”, .250” .375”, .500” |
| Arbor Size | 1” with Drive Pin Hole |
| Weight | 200 lb |






P: 877-817- 6687 F: 813-621-7125
Visit us at www.ussaws.com
sales@ussaws.com