


U.S.SAWS Dual Component Polymer Pump



The U.S.SAWS Dual Component pump was designed to be easy to use and inexpensive to maintain with savings up to 50% on material costs with components purchased in bulk. It is equipped with 2 6-gallon tanks to allow you to add a full 5 gallons of joint fill material and still have a reserve left in the tanks.



Easy Application



Ergonomic Handle with Start/Stop Switch



Re-buildable Dispensing Manifold



Optional Power Inverter

Features:

- The Polymer Pump can save up to 50% on material costs with components purchased in bulk
- The unit comes standard with a 1:1 component ratio, but a 2:1 component ratio is available
- Aluminum mixing manifold is easy to maintain and clean
- The dispensing wand has a variable speed control, and start/stop control
- Production rates can range from 4,000 to 7,000 lineal feet per day

Model	Dual Component Polymer Pump
Part Number	SX20100
Power Source	1/2 HP Electric Motor
Power Requirements	110V, 60 Hz
Other Power Options	Gas Generator or Deep Cycle Marine Battery with Power Inverter
Frame	Steel
Tanks	6.5 Gallon Polyethylene
Manifold	Re-Buildable, One-Piece, Aluminum Dispensing Manifold
Compatible Materials	Polyurea and Epoxy Joint Fillers

