

U.S.SAWS™

U.S.SAWS Cut Vac Assembly



PN: SX70000K

The U.S.SAWS Cut Vac is designed to clean out joints and cut and remove existing joint filler in a faster and more accurate cut. The hand-held saw makes for more of a versatile hand-held dust-free saw for routing random cracks, decorative concrete cutting, and joint clean-up. The joint cleanout saw max cutting depth is 1-1/8".

The joint cleanout mill is perfect for indoor joint work because its up-cut rotation allows debris to be removed from joints as you move forward. The Cut Vac is a favorite among decorative concrete contractors and coating contractors for cutting termination cuts or honoring existing fittings in floor coatings.

Features

- Versatile hand-held dust-free saw for: routing random cracks, decorative concrete cutting, and joint cleanout
- Dolly mount (optional) for joint cleanout, straight-line cutting, decorative concrete
- Attaches easily to dust collectors (sold separately) for a cleaner worksite
- 1-1/8" maximum cutting depth with 8" blade
- Adjustable depth shoe
- Uses dry diamond blades
- Assembly includes Metabo W24-180 grinder and shroud



PN: SX70000

Model	Cut Vac
Part Number	SX70000/ SX70000K
Description	Hand-Held Crack Chaser
Grinder/Motor Make/Model	Metabo W24-180
Power Source	15 Amp 110V Electric
Max RPM	8,500
Max Cutting Depth	1-1/8"
Blade Diameter	7" or 8"
Blade Width	.250", .375"
Blade Arbor	7/8"
Weight	27 lb/ 47 lb

