

U.S.SAWS™

U.S.SAWS Mark-III Dust Buggy

The U.S.SAWS Mark-III Dust Buggy is a revolutionary product changing the way we clean-out joints and cut concrete. Our new and improved Mark-III Joint Clean-out machine is the third generation of the famous “Dust Buggy.” The Mark-III is designed to clean-out joints and cut remove existing joint filler faster and more accurately. A specially designed blade guard allows the operator to see the blade yet still covers 98% of it for excellent dust control. The handle was redesigned for more stability, adjustable height, and rotates to get closer to walls or racks. The joint clean-out saw cuts up to 2” deep. The concrete clean-out saw fully complies with ANSI diamond blade speed regulations.



Features


- Electric, portable joint clean-out saw ideal for joint clean-out, joint filler removal, decorative concrete, and concrete cutting
- Adjustable blade depth with up to 2” cutting depth with 8” blade
- Powered by a Metabo 15 Amp 24-230
- Up-cut blade rotation cleans debris out of the joint
- Solid aluminum chassis provides a durable and stable machine to allow for straight, accurate cuts
- Vacuum port allows for dust-free operation



Equipped with Metabo



Aluminum Alloy Chassis



Rotating Handle



Vacuum Port

Production rates vary but a good operator can easily clean out 10,000 linear feet of new, unfilled joints in an 8-hour shift.

MADE IN USA 25 Year Warranty on Chassis

| Model | Mark-III Dust Buggy |
|---------------------|----------------------|
| Part Number | SX13700 |
| Grinder Make/ Model | Metabo W24-230 |
| Output Power | 15 Amp Electric |
| Max RPM | 6,600 |
| Power Requirements | 115V, 60Hz |
| Max Cutting Depth | 2” |
| Blade Diameter | 7” or 8” Dry Diamond |
| Blade Width | .090”, .125”, .250” |
| Blade Arbor | 7/8” |
| Weight | 56 lb |

